Printing date: 07/28/2016 Revision: 02/01/2019

1 Identification

· Product identifier

· Trade name: Bar's Leaks® Head Gasket Sealant

· Product code: 1100

· Recommended use and restriction on use

· Recommended use: Sealant

· Restrictions on use: No relevant information available.

Details of the supplier of the Safety Data Sheet

Manufacturer/Supplier:

Bar's Products P.O. Box 187 Holly, MI 48442 USA Phone: (810) 603-1321

· Emergency telephone number:

ChemTel Inc.

(800)255-3924, +1 (813)248-0585



2 Hazard(s) identification

· Classification of the substance or mixture

The product is not classified as hazardous according to the Globally Harmonized System (GHS).

- · Label elements
- · GHS label elements None.
- · Hazard pictograms: Not regulated.
- · Signal word: Not regulated.
- · Hazard statements: None.
- · Precautionary statements: Not regulated.
- · Other hazards There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Components:			
	silicic acid, sodium salt	10-25%	
	♦ Met. Corr.1, H290; Skin Corr. 1B, H314; Eye Dam. 1, H318		
9004-34-6	Cellulose	<2%	
7440-50-8	copper	<1%	

Additional information:

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret. For the wording of the listed Hazard Statements refer to section 16.

(Cont'd. on page 2)

Printing date: 07/28/2016 Revision: 02/01/2019

Trade name: Bar's Leaks® Head Gasket Sealant

(Cont'd. of page 1)

4 First-aid measures

- Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Wash with soap and water.

If skin irritation is experienced, consult a doctor.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

Most important symptoms and effects, both acute and delayed:

Slight irritant effect on eyes.

Slight irritant effect on skin and mucous membranes.

Gastric or intestinal disorders

Nausea in case of ingestion.

· Indication of any immediate medical attention and special treatment needed:

No relevant information available.

5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · For safety reasons unsuitable extinguishing agents: None.
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

Particular danger of slipping on leaked/spilled product.

For large spills, use respiratory protective device against the effects of fumes/dust/aerosol.

Environmental precautions:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of the collected material according to regulations.

(Cont'd. on page 3)

Page: 3/9

Safety Data Sheet acc. to OSHA HCS (29 CFR 1910.1200)

Revision: 02/01/2019 Printing date: 07/28/2016

Trade name: Bar's Leaks® Head Gasket Sealant

(Cont'd. of page 2)

Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- Handling
- Precautions for safe handling:

Prevent formation of aerosols.

Avoid splashes or spray in enclosed areas.

Use only in well ventilated areas.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- Storage
- · Requirements to be met by storerooms and receptacles:

Avoid storage near extreme heat, ignition sources or open flame.

Information about storage in one common storage facility:

Store away from foodstuffs.

Do not store together with oxidizing and acidic materials.

- · Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.
- · Specific end use(s): No relevant information available.

8 Exposure controls/personal protection

· Control paran	· Control parameters				
· Components w	· Components with limit values that require monitoring at the workplace:				
9004-34-6 Cellulose					
PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction				
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction				
TLV (USA)	Long-term value: 10 mg/m³				
EL (Canada)	Long-term value: 10* 3** mg/m³ *total dust, **respirable fraction				
EV (Canada)	Long-term value: 10 mg/m³ paper fibre, total dust				
LMPE (Mexico)	Long-term value: 10 mg/m³				
7440-50-8 copp	per				
PEL (USA)	Long-term value: 1* 0.1** mg/m³ as Cu *dusts and mists **fume				
		(Cont'd. on page 4)			

Printing date: 07/28/2016 Revision: 02/01/2019

Trade name: Bar's Leaks® Head Gasket Sealant

	(Cont'd. of page 3
REL (USA)	Long-term value: 1* 0.1** mg/m³ as Cu *dusts and mists **fume
TLV (USA)	Long-term value: 1* 0.2** mg/m³ *dusts and mists; **fume; as Cu
EL (Canada)	Long-term value: 1* 0.2** mg/m³ *dusts and mists; **fume, as Cu
EV (Canada)	Long-term value: 0.2* 1** mg/m³ as copper, *fume;**dust and mists
LMPE (Mexico)	Long-term value: 0.2* 1** mg/m³ *humo (como Cu);**polvo y niebla (como Cu)

- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- **Engineering controls:** No relevant information available.
- Breathing equipment:

Not required under normal conditions of use.

Use suitable respiratory protective device when aerosol or mist is formed.

For spills, respiratory protection may be advisable.

Protection of hands:

Wear protective gloves to handle contents of damaged or leaking units.

Gloves are advised for repeated or prolonged contact.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Eye protection:



Safety glasses

· Body protection:

Not required under normal conditions of use.

Protection may be required for spills.

- Limitation and supervision of exposure into the environment No special requirements.
- · Risk management measures No special requirements.

9 Physical and chemical properties

Information on basic physical and chemical properties

· Appearance:

Form: Suspension Color: Red-brown
Odor: Mild

(Cont'd. on page 5)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 07/28/2016 Revision: 02/01/2019

Trade name: Bar's Leaks® Head Gasket Sealant

		(Cont'd. of page
Odor threshold:	Not determined.	
pH-value at 20 °C (68 °F):	<11	
Melting point/Melting range:	Not determined.	
Boiling point/Boiling range:	>104 °C (>219 °F)	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not applicable.	
Auto-ignition temperature:	Not determined.	
Decomposition temperature:	Not determined.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits		
Lower:	Not determined.	
Upper:	Not determined.	
Oxidizing properties:	Not determined.	
Vapor pressure:	Not determined.	
Density at 20 °C (68 °F):	1.37 g/cm³ (11.433 lbs/gal)	
Relative density:	Not determined.	
Vapor density:	Not determined.	
Evaporation rate:	Not determined.	
Solubility in / Miscibility with		
Water:	Fully miscible.	
Partition coefficient (n-octanol/water): Not determined.		
Viscosity		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Other information	No relevant information available.	

10 Stability and reactivity

- · Reactivity: No relevant information available.
- · Chemical stability: Stable under normal temperatures and pressures.
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

Possibility of hazardous reactions:

Toxic fumes may be released if heated above the decomposition point.

Reacts with strong acids and oxidizing agents.

- · Conditions to avoid: Avoid acids.
- · Incompatible materials: No relevant information available.
- · Hazardous decomposition products:

Carbon monoxide and carbon dioxide

(Cont'd. on page 6)

Printing date: 07/28/2016 Revision: 02/01/2019

Trade name: Bar's Leaks® Head Gasket Sealant

(Cont'd. of page 5)

Toxic metal oxide smoke

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification: None.
- · Primary irritant effect:
- · On the skin: Slight irritant effect on skin and mucous membranes.
- · On the eye: Slight irritant effect on eyes.
- · Sensitization: Based on available data, the classification criteria are not met.
- · Carcinogenic categories
- IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

· Probable route(s) of exposure:

Ingestion.

Inhalation.

Eye contact.

Skin contact.

- · Repeated dose toxicity: No relevant information available.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity: Based on available data, the classification criteria are not met.
- · Reproductive toxicity: Based on available data, the classification criteria are not met.
- STOT-single exposure: Based on available data, the classification criteria are not met.
- STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · Aspiration hazard: Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
- · Aquatic toxicity No relevant information available.
- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- \cdot Mobility in soil: No relevant information available.
- Additional ecological information
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Cont'd. on page 7)

Page: 7/9

Safety Data Sheet acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 07/28/2016 Revision: 02/01/2019

Trade name: Bar's Leaks® Head Gasket Sealant

(Cont'd. of page 6)

· Other adverse effects: No relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Smaller quantities can be disposed of with household waste.

Small amounts may be diluted with plenty of water and washed away. Dispose of bigger amounts in accordance with Local Authority requirements.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

- Uncleaned packagings
- **Recommendation:** Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information			
· UN-Number · DOT, ADR, IMDG, IATA	Not regulated.		
· UN proper shipping name · DOT, ADR, IMDG, IATA	Not regulated.		
Transport hazard class(es)			
· DOT, ADR, IMDG, IATA · Class	Not regulated.		
· Packing group · DOT, ADR, IMDG, IATA	Not regulated.		
· Environmental hazards · Marine pollutant:	No		
· Special precautions for user	Not applicable.		
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.			

(Cont'd. on page 8)

Printing date: 07/28/2016 Revision: 02/01/2019

Trade name: Bar's Leaks® Head Gasket Sealant

(Cont'd. of page 7)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 304 (emergency release notification):

None of the ingredients are listed.

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act)

All ingredients are listed.

- · Proposition 65 (California)
- · Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency):

7440-50-8 copper

D

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Date of preparation / last revision 07/28/2016 / -
- · Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road IMDG: International Maritime Code for Dangerous Goods

(Cont'd. on page 9)

Page: 9/9

Safety Data Sheet acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 07/28/2016 Revision: 02/01/2019

Trade name: Bar's Leaks® Head Gasket Sealant

(Cont'd. of page 8)

DOT: US Department of Transportation IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
LDLo: Lowest Lethal Dose Observed
Met. Corr.1: Corrosive to metals – Category 1

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com