

# BAR'S LEAKS® TECHNICAL BULLETIN



Tech Bulletin #: TB-1305	Part Number: 1305
Date Issued: December 28, 2018	Date Revised: n/a
Bar's Leaks® Super Leak Fix™	Size: 16.9 fl. oz. (500 mL)

## Super Leak Fix

Bar's Leaks Super Leak Fix is formulated to work in multiple systems including all Engine Oil, Transmission, Power Steering, Hydraulic and Differential & Gear. Use to stop current leaks, or as a preventative maintenance before leaks start. Premium seal renewing additives are designed to stop seal and gasket leaks caused by normal wear and age. Contains no solids, will not clog filter or harm system.

- **America's Most Trusted Stop Leak Brand Since 1947**
- **Multi-System Formula / 5X Sealer**
  - Engine
  - Transmission
  - Power Steering
  - Hydraulic
  - Gear & Axle
- **Safe and Easy To Use / Will Not Harm Seals**
- **Spout / Hose Included for Easier Application**

Helps with small leaks (if you need to add fluid 1x per month), medium leaks (if you need to add fluid 1x per week), preventative maintenance (to prevent future leaks from happening) with engine oil (gasoline, hybrid, diesel), transmission fluid (automatic, manual, CVT), power steering fluid (pump, gear box, rack & pinion), hydraulic (jack, snow plow, tractor, construction), and gear (differential, axle, gearbox, transfer case).



## Instructions For Use

Fill hose included for easier application in some vehicles. Shake well. Add Super Leak Fix to leaking system per dosage chart. Do not overfill. Leaks usually stop in 200 miles, or 2 days of usage. If leak continues, second application may be required or mechanical attention is needed. **WARNING:** Do not use in brake system or add to antifreeze / coolant.

## Dosage

- Engine and Transmission—Use Full Bottle
- Power Steering—Use 1/2 Bottle
- Hydraulic, Differential, Small Engines—Use 3 to 4 Ounces Per Quart of Capacity
- Preventative Maintenance—Use 1/2 Recommended Dosage