



Tech Bulletin #: TB-HDC	Part Number: HDC
Date Issued: January 22, 2020	Date Revised: n/a
Bar's Leaks® Radiator Stop Leak Tablets	Size: 2.1 OZ (60g)

Radiator Stop Leak Tablets

Bar's Leaks Cooling System Radiator Stop Leak Professional Strength Formula tablets inhibit the formation of rust and scale, neutralize pH imbalance, control electrolysis, lubricate and seal internal, external and coolant-to-oil leaks. Same tablets as used by many OEM auto and truck manufacturers around the world. Bar's Leaks Radiator Stop Leak is designed to enhance the use of antifreeze or can also be used in water. When used in water alone, it is also recommended to use a cooling system anti-rust and water pump lube.

- Professional Strength Formula
- Works with All Types of Antifreeze
- OEM Used and Approved
- Seals Leaks and Seepage
- Helps Control Electrolysis
- Lubricates Water Pump Seal
- Inhibits Rust & Corrosion
- Harmless to ALL Plastic, Metals, Aluminum, Hoses & Connections



Works with ALL Brands and colors of regular and extended life Antifreeze coolant and/or water.

DIRECTIONS: Cooling systems that are dirty or partially clogged should be flushed before usage.

1. Remove radiator cap when engine is cool.
2. Install 2 tablets in radiator for each gallon of cooling system capacity. If vehicle does not have a regular radiator cap, remove top hose where it attached to radiator and insert tablets in hose and then reinstall hose. Tablets may be crumbled or pre-dissolved for easier application.

NOTE: Most vehicles will use all six tablets.

3. Fill radiator and reservoir to proper level.
4. Reinstall radiator cap.
5. Drive/idle engine for 15 minutes at normal operating temperature.
6. If leak persists, a second application may be necessary.

DOSAGE:

One package treats systems up to 3 gallons. For larger systems use 2 (two) tablets per gallon of coolant.