



## BAR'S LEAKS® TECHNICAL BULLETIN

Tech Bulletin #: TB-1199	Part Number: 1199
Date Issued: August 3, 2023	Date Revised: n/a
Bar's Leaks® Radiator Stop Leak	Size: 11 FL OZ (325 mL)

### Radiator Stop Leak

Bar's Leaks® Cooling System Radiator Stop Leak seals internal, external and coolant-to-oil leaks. Works safely and effectively on plastic, aluminum and metal radiators, heater cores, blocks, heads, gaskets and freeze plugs. Compatible with both conventional silicate-based and extended life (OAT/HOAT) antifreeze, all types and colors. Can also be used in straight water.

**Protects the Entire Cooling System**

**Stops Current and Future Leaks**

**Lubricates Water Pump Seal**

**Helps Control Electrolysis**

**Use on Cars, Trucks, Vans SUV's & RV's**

**DANGER:** Opening the cooling system while the engine is hot or running may cause severe burns.

**NOTE:** Cooling systems that are dirty or partially clogged should be flushed before usage.

#### INSTRUCTIONS:

Pour Stop Leak into a cool radiator. If direct access to radiator is not available, install in overflow tank. One bottle treats up to 4 gallons. Use 1/2 bottle for four cylinder engines. Fill radiator and overflow tank to proper level and reinstall cap. Drive/idle engine for 15 to 30 minutes. If leak continues, second application may be required or mechanical attention is needed. Leave Bar's Leaks in cooling system for continued protection.

#### DOSAGE:

Use one bottle for 6, 8 and 10 cylinder gas or diesel engines.

3, 4 and 5 cylinder engines, use 1/2 bottle.

One bottle treats systems up to 4 gallons.

For larger systems use one bottle for every 3 gallons of cooling system capacity.

